

科力达激光扫平仪

高准度测平 稳定性好

液晶
显示

自动
电子
安平

续航
持久

智能
机芯

强防
水性



TRL 155




TRL 131/TRL 134



广东科力达仪器有限公司

地址:广州市天河区思成路39号地理信息产业园8楼
电话:020-22131700 传真:020-22131709
邮箱:kolida@163.com
网址:www.kolida.com.cn

型号	TRL 131	TRL 134	TRL 155
外观			
激光类别/波长	class IIIA/635nm	class IIIA/635nm	class IIIA/635nm
工作距离(直径)	600m	600m	600m
自动安平范围	±5°	±5°	±5°
自动安平精度(10m处)	水平±1mm	水平±1mm;垂直±1mm	水平±1mm;垂直±1mm
激光下对点精度	—	±1mm/1.5m	±1mm/1.5m
手动变坡(双向)	±10%	±10%	±10%
斜坡范围/斜坡精度(双向)	±10%;0.1%	±10%;0.1%	±10%;0.01%
旋转速度(每分钟转速)	5,300,600,1000rpm	5,300,600,1000rpm	5,300,600,1000rpm
区间扫描	0, 15°, 45°, 90°, 180°	0, 15°, 45°, 90°, 180°	0, 15°, 45°, 90°, 180°
遥控距离	—	30m	30m
液晶屏	—	—	FSTN
接口	5/8"接口*2	5/8"接口*2	5/8"接口
电源	7.4v (4400mAH)锂电池组	7.4v (4400mAH)锂电池组	7.4v (4400mAH)锂电池组
外接电源	12v直流	12v直流	12v直流
持续工作时间	30小时	30小时	30小时
工作温度	-10°C~40°C	-10°C~40°C	-10°C~40°C
防水防尘等级	IP54	IP54	IP65
尺寸	225(L)*175(W)*210(H)mm	225(L)*175(W)*210(H)mm	190(L)*235(W)*235(H)mm
重量(含电池)	2.7kg	2.7kg	3.5kg

应用范围

